

Amhaze Stadium 2X IP

A rugged and compact IP-rated hazer built into a self-contained flight case, offering precise DMX and manual control over its variable haze output and blower speed. Designed for the demands of touring, stadiums, festivals, and large-scale productions where a reliable, high-output, and weather-resistant atmospheric effect is essential.

- Ensures exceptional reliability with a serviceable heater core and corrosion-resistant peristaltic pump.
- An adjustable vent louver allows for precise directional control of the haze flow.
- Supports DMX and RDM protocols, with a USB-C port for fast, in-field software updates.
- Achieves operational readiness in just 6 minutes with a powerful 164 cfm fan output.
- Features a full-color display for intuitive onboard adjustments and system status monitoring.
- An integrated low fluid shutdown sensor automatically protects the pump from running dry.



SPECIFICATIONS

Dynamic Effects

Fan Performance: 164 cfm

Low Fluid Shutdown: Yes

Construction / Physical

Dimensions: 26 x 16 x 6.75 in (660 x 406 x 171.45 mm)

Weight: 48.8 lb (22.13 kg)

Exterior Color: Black

Housing Material: Aluminum alloy, Aluminum diecast, High-impact flame-retardant polymer, Steel

Tank Capacity: 1.32 gal (5 l)

Fluid Consumption: 9.5 ml/min

Maximum Runtime: 8 hrs

Connections

Power Connection: Edison (Local) plug to Seetronic Powerkon (powerCON Compatible)

Power Input: Seetronic Powerkon IP65

Data Connectors: 5-pin IP65 XLR

Cable Length (power): 5 ft (1.5 m)

Firmware upgrades: USB type-C

Control

Control Protocol: DMX, RDM

DMX Channels: 2

Modes/Personalities: 1 personality (2ch)

On-Board Control: Yes

Electrical

Input Voltage:

Electrical Detail: 120 VAC, 60 Hz

Electrical Detail 2: 230 VAC, 50 Hz

Power and Current:

Electrical Detail: 511 W, 4.26 A @ 120 V, 60 Hz

Electrical Detail 2: 722 W, 3.14 A @ 230 V, 50 Hz [1.2 A inrush]

Heat-up Time: 6 min

Fuse:

120V model: F8 A, 250 V

230V model: F5 A, 250 V

Certifications / Qualifications

Certifications: CE, UKCA

IP Rating: IP65, temporary outdoor/wet use

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Required Accessories

Accessories (required): Fog Fluid-PHF

Compatible Mounting Options: M12 / ½" hole with mounting brackets (clamps)

Optional Accessories

Neutrik powerKON cables

DMX Cables

What's Included

Amhaze Stadium II IP
Seetronic IP 65 Powerkon power cord
2x Mounting brackets
Output nozzle assembly
Front Cover