

# Cloud 9X IP

A compact, IP-rated low-lying fogger that creates dense, floor-hugging fog using only tap water and specialized fluid, eliminating the need for dry ice or CO2.

Ideal for professional touring productions, event stages, and ballrooms requiring a reliable, continuous low-fog effect without the logistical challenges of dry ice.



- Generates continuous low-lying fog capable of covering a 3,230 square foot area.
- Reaches operational temperature in just five minutes for rapid event deployment.
- Automates refilling with a direct garden hose connection for unattended operation.
- Offers versatile control via DMX, RDM, onboard display, and included wireless remote.
- Housed in a rugged, integrated flight case with a stackable design for touring.
- Simplifies cleanup using an integrated water drainage system with a durable brass fitting.

## SPECIFICATIONS

### Dynamic Effects

**Fan Performance:** 81 cfm

**Low Fluid Shutdown:** Yes

### Construction / Physical

#### Dimensions:

**Dimensions (without back cover):** 30 x 17.36 x 19.22 in (762 x 441 x 488.1 mm)

**Dimensions (with back cover):** 37.72 x 17.36 x 19.22 in (958 x 441 x 488.1 mm)

**Output Nozzle (Outer Diameter):** 4.76 in (121 mm)

**Hose Length (Fully extended):** 11 ft (3.4 m)

**Weight:** 76.6 lb (34.75 kg)

**Exterior Color:** Black

**Housing Material:** Aluminum alloy, High-impact flame-retardant polymer

#### Water Tank Capacity:

**(Primary Tank):** 4.91 gal (18.6 L)

**(Reserve Tank):** 2.41 gal (9.1 L)

**(Total):** 7.32 gal (27.7 l)

**Tank Capacity (Low-lying Fog Fluid):** 0.8 gal (3 l)

**Fog Fluid Consumption:** 25 mL/min (0.88 fl oz/min)

**Fog Fluid Runtime (Fog Fluid Tank, 3 L):** 2 hr

**Water Consumption:** 184.7 mL/min (6.25 fl oz/min)

**Water Runtime (w/ Total Water Tank, 27.7 L):** 2.5 hr

### Connections

**Power Input:** Seetronic Powerkon IP65

**Data Connectors:** 3-pin/5-pin IP rated

**Cable Length (power):** 5 ft (1.5 m)

**Firmware upgrades:** USB type-C

### Control

**Control Protocol:** DMX, RDM, Wireless Remote

**DMX Channels:** 3

**Modes/Personalities:** 1 personality (3ch)

**On-Board Control:** Yes

**Included Remote:** Yes

### Electrical

**Input Voltage:** 120 VAC, 60 Hz

**Input Voltage:** 230 VAC, 50 Hz

**Power and Current:** 1960 W, 17.5 A @ 120 V, 60 Hz

**Power and Current:** 1281 W, 5.59 A @ 230 V, 50 Hz

**Heat-up Time:** 5 min

**Breaker Size:** 10 A, 250 V

### Certifications / Qualifications

**Certifications:** CE, ROHS, UKCA

**IP Rating:** IP54, temporary outdoor/wet use

**Temperature (Ambient):** -4 °F to 113 °F (-20 °C to 45 °C)

### Required Accessories

Accessories (required): Fog Fluid-LLG

Compatible Mounting Options: Floor Mount/Positioning only w/locking wheels

### Optional Accessories

Neutrik powerKON cables

DMX Cables

## What's Included

Cloud 9 X IP

Seetronic Powerkon IP65 power cable

RF remote (2-button)

2 pcs. hose clamps, 6 in (152 mm) diameter

Barbed hose adapter (0.5 in) (13 mm) diameter

2 pcs. barbed hose adapter hose clamp 1 in(25 mm) diameter

6ft (2m) output hose, 5 in, (130 mm) diameter

Removable rear cover

Hose coupler, 5 in (130mm) diameter

Floor nozzle, 5 in (130mm) diameter

Overfill hose (polyurethane, 6mmOD, 4mm ID, 80 in / 204 cm)

Quick Reference Guide