

## Net-X II

A versatile rack-mountable Ethernet-to-DMX node and merger that converts Art-Net or sACN to eight individually assignable DMX outputs and supports DMX preset recording. Perfect for creating a reliable and highly customizable network infrastructure for complex lighting control systems in touring, production, and installation environments.

- Features two 5-pin DMX inputs and eight optically isolated 5-pin DMX outputs.
- Converts up to eight DMX universes into Art-Net or sACN network protocols.
- Merges two controllers using HTP or LTP protocols for flexible signal management.
- Records up to 10 DMX presets for standalone playback or remote contact triggering.
- Supports RDM over Art-Net for simplified remote fixture configuration and management.
- Includes an integrated webserver for remote setup, system backup, and firmware updates.



### SPECIFICATIONS

#### Construction / Physical

**Dimensions:** 19 x 6.22 x 1.73 in (483 x 158 x 44 mm)

**Weight:** 4.6 lb (2.1 kg)

**Threaded Bolt:** M12

**Exterior Color:** Black

**Housing Material:** Steel

**Rackmount:** 1U

#### Connections

**Power Connection:** Edison (Local) plug to Seetronic powerKON

**Power Input:** Seetronic powerKON

**Device Data Inputs:** Seetronic powerKON® (1 total) and 5-pin XLR (2 total)

**Device Data Outputs/Inputs (Assignable):** 5-pin XLR (8 total)

**Device Data Throughputs:** Seetronic etherKON (1 total)

**Cable Length (power):** 5 ft (1.5 m)

#### Control

**Control Protocol:** Art-Net, DMX, sACN

**Merge Support:** Yes

**Protocol Merging:** (2) Art-net consoles, (2) DMX consoles, (2) sACN consoles

#### Electrical

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Power and Current:** 11 W, 0.09 A @ 120 V, 60 Hz

**Power and Current:** 14 W, 0.06 A @ 208 V, 60 Hz

**Power and Current:** 14 W, 0.06 A @ 230 V, 50 Hz

#### Certifications / Qualifications

**Certifications:** CE

**IP Rating:** IP20, dry location

**Temperature (Ambient):** -4 °F to 113 °F (-20 °C to 45 °C)

#### Required Accessories

Compatible Mounting Options: M12 Bolt/Clamp

#### Optional Accessories

Clamps

Neutrik powerCON cables

Neutrik etherCON cables

DMX Cables

#### What's Included

Net-X II

Seetronic powerKON power cord

Phoenix connector