

## Ovation Rêve P-3 IP



A high-output, IP65-rated LED PAR fixture that delivers multi-color and full-spectrum-white light with exceptional color rendering and versatile beam shaping via four interchangeable lenses.

This powerful instrument is perfectly suited for indoor or outdoor theatrical productions, houses of worship, special events, and rental applications, especially where on-camera performance is critical.

- Delivers linear color temperature presets from 2800 K to 8000 K with high CRI.
- Features a fully IP65-rated housing for dependable, all-weather use in any environment.
- Includes four interchangeable lenses to easily adapt beam angles from narrow spot to wide flood.
- Adjustable Pulse Width Modulation (PWM) ensures flicker-free operation for broadcast and film.
- Offers flexible integration with DMX and RDM control across nine operating personalities.
- An advanced RGBAM LED engine provides full-spectrum color mixing and superior white light.

### SPECIFICATIONS

#### Optical

**Light Source:** 80 LEDs (10 red, 10 green, 10 blue, 20 amber, 30 mint) 4.4 to 7.8 W, (2.4 A), 50,000 hours life expectancy.

**Color Temperature (range):** 2800 to 8000 K

**Color Temperature (at full):** 5399 K

**Selectable PWM:** 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

#### Narrow Lens:

**Beam Angle:** 11.9°

**Field Angle:** 20.8°

**Lumens:** 10,051

#### Medium Lens:

**Beam Angle:** 25.6°

**Field Angle:** 37.8°

**Illuminance:** 1,950 lux @ 5 m

**Lumens:** 10,079

#### Wide Lens:

**Beam Angle:** 29.3°

**Field Angle:** 43.1°

**Illuminance:** 1,475 lux @ 5 m

**Lumens:** 9,936

#### Very Wide Lens:

**Beam Angle:** 43.5°

**Field Angle:** 87.9°

**Illuminance:** 401 lux @ 5 m

**Lumens:** 8,380

#### Dynamic Effects

**Dimmer:** Electronic

**Shutter/Strobe:** Electronic

**Strobe Rate:** 0 to 25 Hz

**Standalone Color Mixing:** Yes

**Color Temperature Presets:** Yes

**Dim Modes:** 4

**Built-in Automated Programs:** Yes

#### Construction / Physical

**Dimensions:** 18.82 x 11.81 x 8.27 in (478 x 300 x 210 mm)

**Weight:** 21.4 lb. (9.8 kg)

**Exterior Color:** Black

**Housing Material:** Aluminum diecast

**Accessory Holder/Gel Frame Size:** 7.5 in (191 mm)

#### Connections

**Power Connection:** Edison (Local) plug to Seetronic Powerkon IP65

**Power Input:** Seetronic Powerkon IP65

**Power Output:** Seetronic Powerkon IP65

**Data Connectors:** 5-pin XLR

**Cable Length (power):** 5 ft (1.5 m)

**Software Connection:** USB

## Control

**Control Protocol:** DMX, RDM

**DMX Channels:** 1, 4, 5, 7, 11, 13ch1, 13ch2, 17 or HSV

**Modes/Personalities:** 9 personalities (1, 4, 5, 7, 11, 13ch1, 13ch2, 17, HSV)

## Electrical

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Power Linking:** 5 units @ 120 V; 8 units @ 208 V; 9 units @ 230 V;

**Power and Current:** 274 W, 2.31 A @ 120 V, 60 Hz

**Power and Current:** 267 W, 1.38 A @ 208 V, 60 Hz

**Power and Current:** 265 W, 1.25 A @ 230 V, 50 Hz

## Certifications / Qualifications

**Certifications:** CE, MET, FCC, UKCA

**IP Rating:** IP65, outdoor/wet, with pressure equalizing M12 GORE valve

## Noise Levels:

**Idle:** 17.4 dB(A) @ 1 m

**Auto:** 30.7 dB(A) @ 1 m

**On:** 31.9 dB(A) @ 1 m

**Off:** 2.3 dB(A) @ 1 m

**Silent:** 11.3 dB(A) @ 1 m

**Temperature (Ambient):** -4 °F to 113 °F (-20 °C to 45 °C)

## Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-07

TRUE1 Style Power Extension Cables

5-pin IP65 DMX Cables

RDM2go

USB Jump Drive

Ovation F 7.5" Barndoor V2

## What's Included

Ovation Reve P-3 IP

Seetronic Powerkon power cord

Omega bracket with mounting hardware

Narrow, Medium, Wide, Very Wide Lens

Gel Frame