




Chassis (6.2 x 12 x 3.7 in.) weighs 6.4 lbs.



Power and protect critical electronics and maintain internet connections during power outages with the UPSA6-850 uninterruptible power supply. The UPS keeps you connected by providing battery backup so you can continue phone calls, check e-mails, and maintain home automation and security systems. Includes USB charging port for mobile devices.

Features:

- **Chassis:** Allows horizontal or vertical placement. Keyholes enable the lightweight (6.4 lbs.) UPS to be mounted on a wall.
- **Receptacles:** Ten (10) NEMA 5-15R receptacles (5 battery backup and 5 surge only)
- **Power Rating:** 850VA (500W)
- **Input Voltage:** 110/120VAC
- **Auto Restart:** After full battery discharge, the UPS automatically restarts when utility power returns.
- **USB Communications:** USB port enables plug and play communications between servers, desktops and the UPS.
- **Touch LCD:** Provides vital monitoring and precise information
- **USB Charging Port:** USB A-type port allows you to charge mobile devices during power outage.
- **Battery Type:** Sealed, maintenance-free lead acid battery
- **Surge Protection:** Guards against lightning, surges and spikes
- **Power Cord:** 6 ft. cord with 5-15P plug
- **Warranty:** Three (3) year warranty on electronics and battery (U.S. and Canada)
- **UL, cUL, Energy Star, TAA compliant**
- **A&E Specifications:** The uninterruptible power supply (UPS) shall be Lowell model UPSA6-850, which shall have a 120VAC power rating and ten NEMA 5-15R receptacles (5 battery backup, 5 surge only). It shall feature a lead acid battery and have run time of ____ minutes (50% load). The chassis shall measure 6.2 x 12 x 3.7 inches. It shall include a six-ft. power cord (5-15P).

Options: (order separately)

- **UPSA6-SNMP-USB:** SNMP card provides remote on/off control and monitoring of critical parameters.
- **UPS-EW-A850:** Extended warranty to 5 years (must purchase simultaneously with UPS).

Model Summary:

Model No.	Description	overall width	overall depth	overall height
UPSA6-850	Standby UPS 850VA (500W)	6.2"	12"	3.7"

Specifications:

LOWELL MODEL NO.:		UPSA6-850
CAPACITY	Power rating	850VA (500W)
INPUT	Voltage	110/120VAC
	Frequency	50/60Hz auto-sensing
OUTPUT	Voltage	110/120VAC
	Waveform	Simulated sine wave
	Frequency	50Hz \pm 1Hz or 60Hz
	Transfer time	2-6ms
BATTERY	Battery type	Sealed, maintenance free lead acid
	Battery quantity/size	(1) 12V 5AH
	Recharge	8 hours to 90% capacity
PHYSICAL	Dimensions (W x D x H)	6.2 x 12 x 3.7 in.
	Weight	6.4 lbs
	Line cord	5-15P (6 ft.)
	Receptacles	(10) NEMA 5-15R receptacles (5 battery backup + 5 surge only)
	USB charging port	USB A-type 5V, 2.4A
ENVIRONMENT	Operating temperature	32–104°F (0–40°C)
	Humidity	0-90%
	Altitude	11,500 ft above sea level
INDICATORS & ALARMS	Display	Touch LCD
	Data line protection	RJ45
APPROVALS		UL, cUL, RoHS, TAA
WARRANTY		3 years electronics and 3 years battery (US and Canada)
COMMUNICATIONS INTERFACE		USB and cable
INCLUDED IN BOX		USB cable

Battery Run Times (minutes):

System Load:	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
UPSA6-850	45	20	12	7.3	6	4	2.5	2	1	<1

NOTE: Run times vary based on battery age and site conditions.

