

Model No.

RMP8A

Mounting ring for 8-in. speaker



PLASTIC MOUNTING RING for recessed installation of an 8-inch speaker with a screw-mount grille in a new or retrofit ceiling or wall is an economical alternative to using a recessed backbox where not required by specifications or code. *Note that speaker installation should always be performed according to all local building codes and regulations, many of which require a backbox*

FEATURES

CONSTRUCTION: Flexible UL94-HB rated ABS plastic ring with U-nuts

DIAMETER: 13.812-inch diameter. *Note: The breakaway groove facilitates threading the ring into a smaller (12.125-inch) diameter opening.*

THICKNESS: 0.375-inches

HARDWARE: Includes 8-32 screw retaining clips

COUNTRY OF ORIGIN: Made in USA

INSTALLATION

ANCHOR HOLES: Locating anchor holes in retrofit and room-side installations can be tricky. Prior to threading the ring through the ceiling, notice the eight outer anchor holes are positioned 1.375-inch out from grille mounting holes. When the ring is installed, grille mounting holes are visible and the anchor holes can be located by measuring 1.375-inch out from the grille holes.

BREAKAWAY GROOVE: Snap the breakaway groove and thread the 13.812-inch diameter ring into a pre-cut 12.125-inch hole. The ring can be held in place and anchored using flush head screws.



Breakaway groove facilitates threading ring into a smaller opening.

A&E SPECIFICATIONS

The mounting ring shall be Lowell model RMP8A, which shall screw-mount an 8-inch speaker with Lowell grille model _____. The mounting ring shall be of flexible UL94-HB rated ABS plastic construction with a breakaway groove that allows the ring to install in a 12.125-inch diameter opening. The ring shall have a 13.812-inch diameter and thickness of 0.375-inches. It shall be equipped with 8-32 screw retaining clips. The outer rim shall have an additional eight mounting holes for application needs.

COMPATIBLE COMPONENTS

- Speakers: Standard 8-inch speaker
- Lowell Screw-Mount Grille Models: A8-AW, CS-8H, LO8-P, RS8-AW, WB-8, WB-8H

WARNING! *Speaker installation should only be performed by experienced qualified professionals with knowledge of load-rated hardware and safe installation, mounting, and rigging techniques. Improperly installed equipment can result in property damage, personal injury, death, and/or liability to the installing contractor. The speaker system must be mounted in accordance with all local, state, and federal codes and regulations and the installation must conform to industry standard practices. It is the responsibility of the installer to furnish all installation hardware, rigging hardware, and safety or restraint cables to be used. Before installation, it is the responsibility of the installer to consult a licensed mechanical or structural engineer to evaluate and certify the structural integrity and safety of any mounting method and the suitability of that method to be used to mount the loudspeaker to the building structure in this particular installation. Lowell Manufacturing is not responsible for the use, misuse, misapplication, or unsafe installation of this loudspeaker product.*



DRAWINGS:

