

## **SPECIFICATIONS**

## **KEY FEATURES:**

- **▶** Large format loudspeaker
- **▶** Long range clarity
- **▶** Synergy crossover network
- **▶** Sentinel<sup>™</sup> Limiter protection circuitry

The SH62 is a high powered, full range loudspeaker that is meant primarily for far throw applications. Where intelligibility is a must at high volume, the SH62 is second to none. It can be configured for passive, bi-amp or tri-amp modes.



## **APPLICATIONS:**

- ▶ Stadia / Arena
- ► Sports Facilities
- ▶ Concerts
- ▶ Theme Parks

Operating Frequency Range	70 Hz – 18kHz +/- 3 dB
	50 Hz – 20 kHz +/-10 dB
Sensitivity	105 dBSPL measured at 1M @ 2.83V input
Maximum Output	138 dBSPL Cont., 144 dBSPL Peak
Recommended Amplifier Power:	2000 Watts continuous, 8000 Watts peak
Drivers	2 x 1.4" HF on Paraline Lense - 6 x 6" Mid - 2 x 15 LF
Input Connections	NL4, NL8
Impedance	4 Ohms
Enclosure Material	Baltic Birch

Performance Data								
Model	MAX SPL	Sensitivity	Magnitude Response	Beam Width	Power Rating	Dimensions	Weight	
SH62	144 dB	105 dB	70 Hz - 18 kHz	60 x 20	8000 W Peak	22.5"H 36"W 30"D	235Ibs	