Product: **25226B**
2 Conductor 14 AWG Stranded Unshielded Plenum
Audio, Sound, Alarm



CONDUCTOR PARAMETERS	
Number of Conductors	2
AWG Size	14
Conductor Stranding	19x27
Conductor Type	Bare Copper
Nominal DCR	2.7 Ω/1000 ft
Twists/ft	4.4 in
INSULATION PARAMETERS	
Insulation Type	Plenum PVC
Insulation Thickness	.012 in
Insulation Color Code	Black, Red
SHIELDING PARAMETERS	
Shield Type	Unshielded
ELETRICAL PARAMETERS	
Nom. Cap. Between Conductors	24 pf/ft

OVERALL CONSTRUCTION PARAMETERS	
Total No. of Conductors	2
Jacket Type	PVC
Nominal Jacket Thickness	.015 in
Nominal Cable O.D.	.223 in
Plenum	Yes
NEC UL Rating	CL2P
RoHS Compliant	Yes
Pull Tension	84 lbs/f
Bend Radius	2.0 in
Bulk Cable Weight	36 lbs

OVERALL ELECTRICAL CHARACTERISTICS	
UL Flammability	NFPA 262 Plenum
Operating Range	0 to 60°C
UL Voltage Rating	300