



25510B

2 Pair 22AWG Individually Shielded CMP Rated
Audio and Control

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Pairs	2
• AWG Size	22
• Conductor Stranding	7x30
• Conductor Type	Bare copper
• Nominal DCR	17 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Plenum PVC
• Insulation Thi kness	0.007 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green
SHIELDING PARAMETER	-
• Shield Type	Individually Shielded
• Drain Wire Type	Tinned Copper
• Drain Wire AWG	24 AWG
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	54 pF/ft
• Nom. Cap. Conductor to Shield	97 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Total Number of Conductors	4
Jacket Type	Flexible Plenum
Jacket Thi kness	0.015 in
Nominal Cable O.D.	0.195 in
Plenum	Yes
NEC UL Rating	CMP
RoHS Compliant	Yes
Bend Radius	1.75 in
Cable Weight	22 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



25510B

2 Pair 22AWG Individually Shielded CMP Rated
Audio and Control

Related Products

RELATED PRODUCTS